




ROOF TILE MACHINE

QUICK SPECIFICATIONS

✓ **TM-500-UNOSP**

500 TILE PACKAGE

- **Maximum Velocity:** 3 tiles per minute
- **Production:** 500 tiles per shift - 8 hour
- **Main Features:** Single profiles; manual handling
- **Installed Power:** 6 kW (mixer included) 380Volt
- **Benefits:** Production of high quality extrusion roof tiles, roof covering $\pm 50m^2$.
- Stationary Machine
- Ideal choice for first time manufactures
- **Starter package includes:**
 1. 500 Aluminium Double Roman Tile Moulds
 2. 25 Ridge Moulds
 3. Pan Mixer
 4. Manual Bench for ridge making



ADDITIONAL INFO

- Operating Staff: ± 6 people (depending on skill levels)

MOULDS:


- The TM-500-UNO-SP comes standard with 500 Double Roman roof tile moulds
- 25 Ridge tile moulds

BENEFITS OF CONCRETE ROOF TILES:

- Eco-friendly
- Thermal excellence and high quality
- Aesthetically pleasing
- Cost effective

ACCESSORIES (AVAILABLE ON REQUEST)

- Manual Demoulding Table
- 1 x Curing Rack for 96 tiles (drawings supplied for remaining racks)
- 1 x Curing Rack for 80 ridges
- Manual Strapper with strap coil
- Hygrometer and thermometer for curing



Double Roman Tile

Ridge Tile



+27 (11) 913 1449



sales@hydraform.com



www.hydraform.com

THE LEADING BUILDING TECHNOLOGY COMPANY, SINCE 1988