



HYDRAFORM

THE LEADING ALTERNATIVE BUILDING TECHNOLOGY, **SINCE 1988**



THE M7

STATIONERY HYDRAFORM BLOCKMAKING MACHINE



- **Features:** Stationary - 10inch wheels for onsite mobility (no towing)
- **Power source:** 13 HP Diesel engine, diesel consumption 2.5 litre/hour or Electric Three Phase 380Volt- 7.5 kW
- **Operating staff:** ± 5 - 8

RECOMMENDED SPARES/ACCESSORIES FOR OPTIMUM PRODUCTION:


- Block cutter | Block tester | Wearplates | Hydraulic filter
- **Accessory products offered by Hydraform available on:**
<https://www.hydraform.com/products/accessories/>

LEADERS IN ENVIRONMENTAL SUSTAINABILITY



PRODUCTION:

- **UP TO 1700 BLOCKS**
PER 9 HOUR DAY
- **UP TO 8 X 50M² HOUSES**
PER MONTH
- *** INCREASE PRODUCTION**
UP TO 2200 BLOCKS
PER DAY WITH A PAN
MIXER AND UP TO 3000
BLOCKS PER DAY WITH
AUTOMATION



DESCRIPTION:

MACHINE SUPPLIED WITH A 150MM, 180MM OR 220MM WIDE INTERLOCKING MOULD OF YOUR CHOICE. OTHER MOULDS ARE AVAILABLE AS PER THE HYDRAFORM PRODUCT LIST.



PROJECT TYPE:

- **START-UP/DIY PROJECT**
- **JOB CREATION**
- **COMMUNITY DEVELOPMENT**



ESTIMATED MACHINE DIMENSION:

LENGTH/WIDTH/HEIGHT CM -
147/132/164 (ELEC)
182/142/164 (DIESEL)
CUBIC METER: 3,182 (ELEC) 4,238 (DIESEL)
ESTIMATED WEIGHT - 508/600



HYDRAFORM



INTERLOCKING BLOCK RANGE

BLOCK	DESCRIPTION	BLOCK APPLICATION
HYDRAFORM 220MM CONDUIT BLOCK		
	<p>Recommended for seismic regions as per engineers specifications.</p> <ul style="list-style-type: none"> No mortar Interlocking Horizontal cavity for rebar, cables or piping. <p>Dimensions are W220 x H115 x L230mm</p>	
HYDRAFORM 180MM CONDUIT BLOCK		
	<p>Recommended for single story construction as per engineers specifications.</p> <ul style="list-style-type: none"> No mortar Interlocking Horizontal- cavity for cables and piping <p>Dimensions are W180 x H115 x L230mm</p>	
HYDRAFORM 150MM CONDUIT BLOCK		
	<p>Recommended for single story construction as per engineers' specifications. Infill between concrete or steel columns.</p> <ul style="list-style-type: none"> No mortar Interlocking Horizontal cavity for rebar, cables or piping. <p>Dimension are W150 x H115 x L230mm</p>	
HYDRAFORM 140MM SEMI DRY-STACK BLOCK		
	<p>Mainly for internal walls and infill. Can also be used for small single-story constructions as per engineer's specification.</p> <ul style="list-style-type: none"> Semi dry-stack Cement slurry between blocks <p>Dimensions are W140 x H115 x L230mm</p>	
HYDRAFORM CORNER LONG BLOCK (1 BLOCK AND A HALF)		
	<p>Long block, can be made with any mould by double loading the chamber</p> <ul style="list-style-type: none"> Used to start the corner of your wall construction. Daily production should be 10% of the full block production (100 corner long blocks for every 1000 normal blocks) <p>Dimensions are 180, 150, 140 x H115 x L280mm</p>	
HYDRAFORM CAPPING 220MM BLOCK		
	<p>Recommended for boundary wall finishing and window sills.</p> <p>Dimensions are W220 x H115 x L230mm</p>	